

Product Datasheet

Item No.: 20743



PRODUCT NAME

Solid rubber armored cable reel 40 m H07BQ-F 3G2,5 IP54



Reference image



- Reel bodies made from extremely durable vulcanized hard rubber material
- Impact-resistant, resistant to oil, grease and petrol, very good insulating properties, unbreakable
- With extremely stable double-tube frame made from 22-mm-thick steel tubing with parking brake
- 2 large crank handles, one of which rotates for easy winding in
- Frame with ergonomic non-slip carry handle and cable guide
- With built-in thermal circuit breaker
- With phase monitoring display
- Cable with polyurethane outer sheath for maximum mechanical stress, extremely weather-resistant, highly flexible, tear-resistant, cut-resistant and abrasion-resistant, in orange safety color
- IP54: protected against dust and splash-proof
- With SCHUKOUltra Pro shock-proof plug 230 V
- With 4 shock-proof socket outlets, splash-proof
- 230 V, 16 A, max. 3,500 W

Technical data

EAN	4011160207433
Weight [kg]	13
Dimensions	31,5x29x37 cm
Main color	black
Category	Cable reels
Subcategory	Solid rubber armoured cable reels
Cable type	H07BQ-F
Cross section [mm²]	3G2,5
Cable color	orange
Cable length [m]	40
Rated voltage [V]	230
Rated current [A]	16
Maximum power	3500 W
Brake	Yes
Drum diameter	290 mmØ
Metal frame	Yes
Thermal fuse	1P
IP protection	IP54
Input	Shock-proof plug SCHUKOUltra Pro 230 V, 16 A, IP54 with 40 m H07BQ-F 3G2,5
Output	4x shock-proof connector with blue protective cap socket insert with voltage indicator, 230 V, 16 A, IP54
Total number of sockets	4
Number of Type F sockets (230 V)	4
Number of cores	3

Your partner for professional lighting and electrical products.

