Product Datasheet

Item No.: **45401**

PRODUCT NAME

PRCD-K extension 1-way 3 m H07BQ-F 3G2,5 IP44

Reference image

- 2x 1.5 m H07BQ-F 3G2.5 heavy-duty polyurethane power cable
- With shock-proof plug and shock-proof connector with protective cap
- With PRCD-K inline RCD (article number 45400)
- 230 V, 16 A, 50 Hz, max. 3500 W
- IP44: protected against foreign bodies and splash-proof

Technical data

EAN	4011160454011
Weight [kg]	0.9
Dimensions	26x6x30 cm
Main color	black
Series	PRCD
Category	Personal protection range
Subcategory	PRCD-K range
Cable type	H07BQ-F
Cross section [mm²]	3G2,5
Cable color	orange
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Maximum power	3500 W
IP protection	IP44
Protection device	PRCD-K inline RCD 30 mA IP55 (art. no. 45400)
Input	Shock-proof plug 230 V, 16 A, IP44
Output	1x shock-proof connector with protective cap 230 V, 16 A, IP44
Total number of sockets	1
Number of Type F sockets (230 V)	1
mA	30

as – Schwabe GmbH Merkurstraße 10 D – 72184 Eutingen Tel. +49 7457 9 48 53 0 office@as-schwabe.de www.as-schwabe.com

Created 21.10.2025. All proprietary rights and the right to make technical changes are reserved. Reproduction is permitted only with the prior consent of as – Schwabe GmbH.