

Product Datasheet

Item No.: 46346



PRODUCT NAME

Optiline mobile LED floodlight 80 W - 9200 lm



Reference image



- LEDs with a lifespan of over 40,000 hours
- Color temperature: 4,000 K (neutral white)
- LED beam angle: 100°
- Color rendering index: CRI > 80
- With polycarbonate diffuser plate
- Extremely slimline floodlight housing made of special plastic and lockable fixing holder
- Power cord and diffuser plate cannot be replaced
- Connection: 220-240 V/50 Hz
- 3 m heavy-duty rubber cable H07RN-F 3G1.5 with shock-proof plug
- IP54: protected against dust and splash-proof

Technical data

EAN	4011160463464
Weight [kg]	3.4
Dimensions	10x37,5x47 cm
Main color	blue
Series	Optiline
Category	Lighting
Subcategory	Optiline floodlight series
Cable type	H07RN-F
Cross section [mm²]	3G1,5
Cable color	black
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Power [W]	80
IP protection	IP54
Input	Shock-proof plug 230 V, 16 A, IP44 with 3 m H07RN-F 3G1,5
Output	2x shock-proof connector with protective cap 230 V, 16 A, IP44
Light color [K]	4000
Luminous flux [lm]	9200
Total number of sockets	2
Number of Type F sockets (230 V)	2

Your partner for professional lighting and electrical products.



as – Schwabe GmbH Merkurstraße 10 D – 72184 Eutingen Tel. +49 7457 9 48 53 0 office@as-schwabe.de www.as-schwabe.com

Created 21.10.2025. All proprietary rights and the right to make technical changes are reserved. Reproduction is permitted only with the prior consent of as – Schwabe GmbH.